## Introducing the alliMaster

Welcome to the new age of Supershear shearing equipment - The TalliMaster Shearing Machine. Supershear, who have designed and manufactured shearing equipment for over 100 years, have now delivered the next age in shearing machine technology.

The TalliMaster combines new age technology and superior engineering, delivering a shearing machine that incorporates advanced performance and shearer safety for the shearing shed environment. The TalliMaster introduces an Electronic Cut-out System (ECS) which when activated, disengages the motor, downtube and handpiece giving the operator a new degree of safety in a shearing situation.

The TalliMaster is a shearing machine that has been purposely designed to deliver a new range of features which will not only improve the Tallies of the shearer but provide the shearing shed with a higher level of safety.

Give the TalliMaster a position in your shed and see the difference in Supershear shearing. TalliMaster - Legendary in it's class!

## Features include:

- Electronic cut-out system (ECS) providing a new level of safety
- New technology providing constant power and torque giving improved performance
- Reduced power consumption ideal for remote areas
- Lightweight construction ease of installation and portability
- Direct drive operation reduces the need to replace parts
- Rapid motor stop feature limiting the stress on other components
- A reduction in noise and heat output gives you a smoother running machine increasing it's lifespan
- Larger pull cord diameter
- Renown Supershear manufacturing quality

## Introducing the ECS

**TalliMaster** 

For a limited time only, when you purchase a new TalliMaster machine, complete with downtube, you will receive a Shearers Back Aid Frame FREE! (valued at \$130 RRP).

Voltage requirements	Standard shed 240V 50Hz supply
Motor type	Ultra reliable 550W industrial motor
Current draw	Super low 1.9A max. Ideal for generator powered sheds.
Speed at downtube	3200 rpm
Total weight of motor assembly	12.5 kg
Bracket system	Welded steel frame.
Wall attachment	Standard Supershear bolt configuration.
Flange mounting	Direct to downtube using standard Supershear attachments.



## For more information please call your local Tru-Test customer service team on 1800 641 324 or visit www.trutest.com.au

Offers valid from 1/2/06 – 31/3/06 or while stocks last (promotional items only available while stocks last).